

## [54] TIME INDEX ACCESS STRUCTURE FOR TEMPORAL DATABASES HAVING CONCURRENT MULTIPLE VERSIONS

[75] Inventors: Ramez A. Elmasri, Houston, Tex.; Tzyh-Jain G. Wu, Manalapan, N.J.

[73] Assignee: Bell Communications Research, Inc., Livingston, N.J.

[21] Appl. No.: 564,881

[22] Filed: Aug. 9, 1990

[51] Int. Cl.<sup>6</sup> ..... G06F 15/40[52] U.S. Cl. .... 395/600; 395/700;  
395/486; 364/419.19; 364/282.1; 364/282.3;  
364/DIG. 1[58] Field of Search ..... 395/600, 650, 725, 425;  
375/107; 364/419.19

## [56] References Cited

## U.S. PATENT DOCUMENTS

3,568,155	3/1971	Abraham	340/172.5
3,681,781	8/1972	Batcher	444/1
4,646,229	2/1987	Boyle	395/600
4,805,107	2/1989	Kieckhafer et al.	395/650
4,894,846	1/1990	Fine	395/107
4,914,586	3/1990	Swinehart et al.	395/600

(List continued on next page.)

## OTHER PUBLICATIONS

"The Ubiquitous B-Tree", D. Comer, *ACM Computing Surveys*, Jun. 1979, pp. 121-137."Efficient Indexing Methods For Temporal Relations", H. Gunadhi & Arie Segev, submitted to *IEEE Transactions On Knowledge and Data Engineering* May 1990."A Taxonomy of Time in Databases", R. Snodgrass & I. Ahn, *ACM SIGMOD Conference*, May 1985, pp. 236-246."A Generalized Model For A Temporal Relational Database", S. Gadia & C. Yeung, *ACM SIGMOD Conference*, Jun. 1988, pp. 251-259.

"Logical Modeling Of Temporal Data", A. Segev &amp; A.

Shoshani, *ACM SIGMOD Conference*, Jun. 1987, pp. 454-466."A Temporal Model And Language For ER Databases", R. Elmasri & G. Wu, *IEEE Data Engineering Conference*, Feb. 1990, pp. 76-83."Design Dbms Support For The Temporal Dimension", V. Lum, *ACM SIGMOD Conference*, Apr. 1984, pp. 115-130.

"Physical Organization Of Temporal Data", D. Rotem

(List continued on next page.)

Primary Examiner—Thomas G. Black

Assistant Examiner—Paul R. Lintz

Attorney, Agent, or Firm—Leonard Charles Suchyta;  
Lionel N. White

[57]

## ABSTRACT

A time index for temporal databases is provided which enables the retrieval of database object versions that are valid during specified time periods. Unlike prior access and retrieval structures, the present index is based on objects whose search values are time intervals rather than time points. A series of ordered indexing points is defined by the start and end of object version intervals and these points are used to build an indexing structure, which may take the form of a B<sup>+</sup>-tree. Each leaf node entry of the B<sup>+</sup>-tree represents an indexing point and has an associated bucket of pointers which identify all object versions that are valid at that time. Storage space is reduced by including only incremental change indicators in the buckets of non-leading leaf entries and calculating needed pointers from such indicators. The time index may be employed in multi-level structures with attribute indexes to greatly improve the efficiency of temporal search operations, such as aggregate functions and temporal selection, as well WHEN and JOIN operators.

14 Claims, 5 Drawing Sheets

